

## EXFW1

### Features and Specifications

#### Applications

For locations where exit signs are needed in a wet or corrosive area.

#### Features

- Sealed and gasketed thermoplastic housing is corrosion and impact resistant.
- Maintenance free sealed nickel cadmium battery.
- Universal chevrons are easily snapped out for directional indication.
- AC only option.
- Battery Back-up option.

#### Certification & Listings

- UL 924.
- Wet Location Listed.
- NEC.

#### Construction

Injection-molded, high impact, UV-stabilized, UL 94 V-o thermoplastic housing. 6" high red or green letters with 3/4" stroke chevron indicators. Single sided only.

#### Electrical

120v or 277 VAC operation. Normal power consumption less than 2 watts. [90] minutes of emergency lighting with "Battery Backup" units.

#### Rated Life

50,000 hours.

#### Warranty

Orion LED fixtures are covered by a five-year limited warranty. Accessories and individual components are covered by separate OEM supplier warranties.



### Part Numbering Example

Product Series	Letter Color	Housing Color	Exit Sign Format	Voltage	Electrical Operation	Mounting Options
<b>EXFW1</b>	<b>RD</b>	<b>W</b>	<b>SSF</b>	<b>UNV</b>	<b>BB</b>	<b>WM</b>

### Ordering Information

Product Series	Letter Color	Housing Color	Exit Sign Format	Voltage	Electrical Operation	Mounting Options
<b>EX</b> = Exit Sign <b>F</b> = F Series <b>W</b> = Wet Location <b>1</b> = Gen 1	<b>RD</b> = Red <b>GN</b> = Green	<b>W</b> = White	<b>SSF</b> = Single sided only	<b>UNV</b> = 120v or 277v	<b>AC</b> = AC only <b>BB</b> = AC normal operation "Battery Back-up" upon power outage [90 min.]	<b>WM</b> = Wall mount



### Physical and Performance Information<sup>1</sup>

LED Exit Color	Output @ 120v-60 hz	Output @ 277v-60 hz	Length	Height	Width	Weight
Red	3.2w	3.0w	11.75"	11.75"	5.25"	3 lbs.
Green	3.8w	3.6w	11.75"	11.75"	5.25"	3 lbs.

### Additional Specification Information

<sup>1</sup> Actual performance may vary by up to +10% of values listed