

# LED TROFFER RETROFIT

ISON™ LED LDR® MODULAR HEALTHCARE

## LDRMH1 SPECIFICATIONS

### Fixture Sizes

- 2' x 2' or 2' x 4'

### Lumen Range / LPW

- 2,000 to 8,000 Lumens

### Factory Installed Features and Options

- 120-277v
- 80 CRI; 4000K
- Matte Opaque Lens Standard
- Vyv Antimicrobial Protection and Britex™ Coating
- Constant Disinfecting of Bacteria and Viruses, Three Different Wavelengths for Different Levels of Disinfecting

### Field Installed Options

- Seismic Cable

### Certifications / Listings\*

- Buy American Compliant
- UL/cUL Listed

### Mounting Options

- Plenum, Lift, and Standard Brackets for T-Bar Grid Ceilings

Britex™ coating comes standard with antimicrobial properties to eliminate contaminants that come in contact with the unit

Installs in minutes with quick bracket system



Vyv Antimicrobial technology kills virus, bacteria and more

Field interchangeable lighting module

*\*Varies by fixture configuration*

800.660.9340 | [orionlighting.com](http://orionlighting.com)

© 2024 Orion Energy Systems, Inc. All right reserved. The Orion logo, ISON™, TritonPro™, and Harris product names are registered trademarks of Orion Energy Systems. All other trademarks are property of their respective owners.

P-INT-XS-151 | Rev. 20241125