



IAHP2 Series LED Area Light EPA Ratings

	Single Head	2 Heads @ 90°	2 Heads @ 180°	3 Heads @ 90°	3 Heads @ 120°	4 Heads @ 90°	2 Heads Side-by-Side	3 Heads Side-by-Side	4 Heads Side-by-Side
Tilt									
A1 / B1 Lumen Code									
0°	0.452	0.685	0.904	1.137	1.016	1.137	0.465	0.698	0.930
10°	0.452	0.685	0.904	1.137	1.235	1.137	0.465	0.698	0.930
30°	1.020	1.473	1.020	1.253	1.803	1.253	2.041	4.418	4.082
60°	1.679	2.131	1.679	1.912	2.462	1.912	3.358	6.394	6.717
90°	1.938	2.390	1.938	2.170	2.721	2.170	3.875	7.169	7.750
C1 / D1 Lumen Code									
0°	0.517	0.814	1.033	1.330	1.192	1.330	0.594	0.891	1.188
10°	0.633	0.814	1.033	1.330	1.528	1.330	0.594	0.891	1.188
30°	1.576	2.093	1.576	1.873	2.471	1.873	3.152	6.278	6.303
60°	2.622	3.139	2.622	2.919	3.517	2.919	5.244	9.416	10.488
90°	3.010	3.526	3.010	3.307	3.905	3.307	6.019	10.579	12.038

Note: All above rating calculations using slipfitter bracket