

Keilton + autani

EFS106 Series

Plug and Play High Bay Sensor



EFS106-BH4
(Lens Sold Separately)



EFS106-AUX
(Lens Sold Separately)



EFS106-Z10
(Lens Sold Separately)

Description

EFS106 low voltage high bay sensors are ideal for Luminaire Level Lighting Control (LLLC/NLC5) applications. Featuring integrated daylight harvesting and PIR motion sensors, the EFS106 sensors are designed for pre-installation in linear high bay or UFO high bay luminaires. EFS106 sensors are equipped with the **AlgoH™** algorithm to maximize detection for high bay applications up to 40 ft without false triggers.

Features

- Plug and Play with sensor port pre-installed
- Bluetooth network technology
- Designed for High Bay applications
- **AlgoH™** algorithm enhances performance in high bay applications
- Built-in analog PIR sensor
- Replaceable lens options
- 12V DC input
- Daylight harvesting available

Requirements


- Lens sold separately
- Requires Dim-to-Off LED drivers with 12V AUX output
- Requires one of the BH4/SC01/Zhaga receptacles

Specifications

Input Voltage	DC 12V
Input Current	50mA Max
Input Power	0.6W
Output Voltage	DC 10V
Output Current	10mA Max
Output Power	0.1W
Dimming	Class 2, 0-10V DC 10mA Max
Sinking Current	10mA Max
Bluetooth Transmit	100ft Max
Radio Frequency	2.4GHz ± 75MHz
Bluetooth Version	4.2/5.0
Housing Material	UL 94-5VA
Detection Range	40-80ft
Mounting Height	20-40ft
Indoor/Outdoor Use	Outdoor Use
Operating Temperature	-30°C to 55°C, -22°F to 131°F
Storage Temperature	-30°C to 85°C, -22°F to 185°F
IP Rating	IP40
Color	White, Black
Warranty	5 year warranty
Compliance	UL8750, RoHS
Safety	cULus Listed LED Controller E504054 FCC ID: 2A26YLTKTVT2021 DID: D057145 DLC: NLTRC5KLOTN




SC03




Dimensions

Unit:inch/mm



EFS106-BH4



EFS106-AUX




EFS106-Z10




Dimensions - Accessories



BH4



SC01-AUX





SC03-AUX




Socket Mounting Dimensions		1/2 inch US standard knockout
Size	T.P.I - inch	Major Dia. - inch
R1/2	14	0.825

Unit:inch/mm


HBL1



Coverage Side View





Coverage Top View




Height 40ft

Dimensions - Accessories


HBL3



Coverage Side View




Coverage Top View



Height 40ft

Detecting Spots For Ref



HBL3 has more detected points than HBL1

Product Label



The Bluetooth word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by LiteTrace is under license. Other trademarks and trade names are those of their respective owners.

App Download



Due to our continued efforts to improve our products, specifications are subject to change without notice.

Contact Us

7090 Columbia Gateway Drive, Suite 140, Columbia, MD 21046, USA

T: +1 443-320-2233 (M-F 9am-5pm ET)

E: support@autani.com

Revised on 6-20-2024