

ECRUB

Features and Specifications

Applications

For locations where exit sign and emergency lighting are needed in the same area.

Features

- Energy efficient LED technology Exit Sign.
- Fully adjustable glare free LED lighting heads.
- Includes maintenance- free NiCad battery.
- Universal chevrons are easily snapped out for directional indication.
- Housing includes extra faceplate for single or dual face application.
- Push-to-test Switch and LED Charge Indicator.
- High lumen.
- Wire guard.

Certification & Listings

- UL Damp Location Listed.
- NEC.

Construction

Injection-molded, high impact, UV-stabilized, UL 94-o thermoplastic housing. 6" high red or green letters with 3/4" stroke chevron indicators. Single or dual sided. Compact low-profile design.

Electrical

120v or 277v VAC operation. Normal power consumption of 5 or less watts. 90 minutes of emergency lighting with battery back-up option.

Ambient Operating Temperature Range

20°C to 30°C [68°F to 86°F]

Rated Life

50,000 hours.

Warranty

Orion LED fixtures are covered by a five-year limited warranty. Accessories and individual components are covered by separate OEM supplier warranties.



Part Numbering Example

Product Series	Letter Color	Housing Color	Exit Sign Format	Voltage	Mounting	Option
ECRUB	RD	W	SDF	UNV	BB	UM

Ordering Information

Product Series	Letter Color	Housing Color	Exit Sign Format	Voltage	Battery Back-up	Mounting
E = Exit and Emergency C = Combination R = Round Heads U = Universal Mount B = Battery Back-up	RD = Red GN = Green	W = White B = Black	SDF = Single and dual-sided formats are standard with all exit signs	UNV = 120v-277v	BB = AC normal operation, "Battery Back" upon power outage (90 minutes)	UM = Universal Canopy Mount included for wall, side or pendent mounting

Options and Accessories

Fixture Option
HL = High Lumen WG = Wire Guard*



*Call Orion representative for details



Physical and Performance Information¹

LED Exit Color	Wattage @ 120v-60 hz	Wattage @ 277v-60 hz	Length	Height	Width	Weight
Red	4.12w	3.2w	17.9"	7.2"	4.34"	2 lbs.
Green	3.22w	3.18w	17.9"	7.2"	4.34"	2 lbs.

LED Emergency Lamps	Wattage @ 120v-60 hz	Wattage @ 277v-60 hz	Length	Height	Width	Weight
Self Powered	5w	4.8w	17.9"	7.2"	4.34"	2 lbs.

Additional Specification Information

¹ Actual performance may vary by up to +10% of values listed