

AHHA

HARRIS LED HIGH BAY HARSH APPLICATIONS, GEN 1



1 BUILT FOR HARSH ENVIRONMENTS
Highly resilient lens gasket made from Fluro-Elastomer FKM material. Best choice when dealing with aggressive chemicals, petroleum lubricants, and solvents in high temperature environments.

2 IP65 RATING
Dust Tight, No Ingress to Dust and Protected against water jets from any direction. UL Wet Listed Fixture.


3 ELECTRICAL
120v to 347v and up to 147 LPW! 6kV/3kA surge protection comes standard per ANSI C82.77-5.

4 DURABLE CONSTRUCTION
Aluminum die cast and glass lens provide maximum protection and heat dissipation for applications up to 50°C (122°F). For a full list of solvents, chemicals, and oils this fixture is resistant against, see our data sheet.




Combined Mounting Options Example


5 CHEMICAL RESISTANT MOUNTING OPTIONS
A Flexible 1/2" trade size non-metallic Polyamide (PA6) flexible conduit for excellent chemical, fuel, and oil resistance
B Standard 1/2" NPT conduit power entry. Conduit sold separately or supplied by customer (must meet chemical resistant requirements)
C U Bracket for surface mount or 1/2" Pendant Conduit Installation
D Hook Mount (for use with U Bracket)



A



B



C



D

