

LED AREA LIGHT

HARRIS AREA LIGHT LUMEN SELECT

ALL P1 SPECIFICATIONS

Fixture Sizes

- 2 Fixture Sizes Available

Lumen Range / LPW

- 12,000 to 42,000 Lumen, up to 158 LPW. Each lumen package allows for field adjustment of lumen output

Factory Installed Features and Options

- 4 Light Distribution Types
- 20-277v or 277-480v
- Bronze Color Standard
- 80 CRI; 3000K, 4000K or 5000K Field Adjustable CCT
- 6kA/10kV Surge Protection Standard
- Factory-Installed, 3-pin Photocell Receptacle with Shorting Cap for Field Installation of Optional Photocell Standard

Field Installed Options

- Light Shield Options Available
- Control and Sensor Options

Control Types Available

- Photocell 120-277v, 347v, and 480v
- Microwave Sensor with Remote Control
- PIR Sensor with Remote Control
- PIR Sensor with Bluetooth Control

Certifications / Listings*

- Dark Sky Compliant
- DLC® Listed Premium
- IK08 Rated
- IP65
- cULus Certified
- UL Wet Rated
- Meets Title 24 Compliance
- Field Adjustable
- CCT

Mounting Options

- Trunnion
- Fixed Universal
- Pole Mount
- Direct Pole Mount
- Slip-fitter
- Adjustable Arm Universal Pole Mount
- Adjustable Wall Mount

Die-cast aluminum housing with powder coat finish for harsh outdoor environments

Two fixture knockouts for easy access to adjust wattage, CCT, and install sensors

Pre-wired sensor receptacle allows for easy screw-in installation. No in-field sensor wiring required

Anti-corrosion stainless steel hardware

Type II, III, IV, and V light distribution



TYPE II

Wide walkways, ramps, and entrance roadways



TYPE III

Perimeter parking areas, parking lots, and roadways



TYPE IV

Perimeter parking areas, and parking lots



TYPE V

Intersections, parking lots, and center roadways

*Varies by fixture configuration