

LED FLOOD LIGHT

HARRIS LED ARCHITECTURAL FLOOD LIGHT, GEN 4

FLGA4 SPECIFICATIONS

Fixture Sizes

- 3 Fixture Housing Sizes



Lumen Range / LPW

- 2,000 to 21,000 Lumens, up to 173 LPW
- Each fixture model allows for field adjustment of lumen output



Factory Installed Features and Options

- 120-277V
- 80 CRI; Field Adjustable CCT from 3000K, 4000K, and 5000K
- Bronze Housing
- Clear Tempered Glass Lens
- Stainless Steel Hardware
- Photocell

Control Types Available

- Dusk-to-Dawn Photocell Standard

Certifications / Listings

- cULus Certified
- UL Wet Rated
- IP65 Rated

Mounting Options

- Pre-installed Knuckle Mount for small and medium housings
- Pre-installed Slipfitter for large housing
- Yoke Mounting Option

Die-cast aluminum housing, stainless steel hardware and glass lens construction to withstand outdoor environments

Accessible dip switches allow the user to select between 3 CCT and 3 lumen outputs in the field



High-performance optics offer NEMA Type 7Hx7V

Integrated standard dusk-dawn photocell provides automated control and maximizes savings. Accessible switch allows it to be turned ON or OFF