

HARRIS LED HIGH BAY STAR LINE HIGH EFFICACY, GEN 1



1 STELLAR NEW PRODUCT LINE
The next level of Harris LED High Bay with competitive array of options with configurability and controllability. Efficacy up to 197 LPW provides best in class return on investment and more energy savings. All this in a compact low-profile fixture.

2 3.5x LIFE*
HHSL1 calculated L70 rating of 219,000 hours is a minimum of 4.4x as long as the typical LED tube retrofit alternative.

3 VERSATILE HANGING OPTIONS
Easy clip-on cables, rigid mount brackets, pendent mount or wire hanger systems available.



HIGH EFFICACY • HIGH EFFICACY • HIGH EFFICACY • HIGH EFFICACY • HIGH EFFICACY

197 LPW



4 CONFIGURABLE POWER CONNECTIONS
Hardwire, power cord whip and plug-and-play power connections available. Configured per order.

5 LIGHT DISTRIBUTION
Available with four light distribution options: No Lens, 120° Lens General Distribution, 50° Lens Narrow Distribution, and 35° Lens Focus Distribution.



9 DURABLE PREMIUM COMPONENTS
Top tier electrical components from suppliers with brand and quality integrity.

7 LIGHTWEIGHT ALUMINUM
Aluminum construction reduces ceiling grid load and maximizes heat transfer to support longer component life. This allows for quick, single person installation minimizing facility disruption due to ease of installation.

8 SUPERIOR THERMAL DESIGN
The Star Line is rated at 55° Celsius with lens vs. most competitors at 40° to 50° Celsius.

6 COMPACT DESIGN
2' and 4' fixture body sizes in a sleek, rigid, linear unibody configuration. Built for multiple ceiling applications.

CONTROLS & ACCESSORIES
Factory or Field Installed options



Available in lumen packages from 9,000 to 20,000 lumens in 2 ft and 24,000 to 45,000 lumens in 4 ft. 120v-277v, 347v, 480v
*LED rated life based on HHSL1D1HEUNVFD L70 @ 25C ambient vs. Orion's TLEDB5 retrofit LED tubes.