HHSL2

HARRIS LED HIGH BAY STAR LINE HIGH EFFICACY, GEN 2

orion INDUSTRIAL

1 STELLAR NEW PRODUCT LINE
The next level of Harris LED High Bay with competitive array of options with configurability and controllability. Efficacy up to 198 LPW at 80 CRI provides best in class return on investment and more energy savings. All this in a compact low-profile fixture.

2 3.5x LIFE*
HHSL2HE calculated L70 rating of 219,000 hours is a minimum of 4.4x as long as the typical LED tube retrofit alternative.

3 VERSATILE HANGING OPTIONS
Easy clip-on cables, rigid mount brackets, pendent mount or wire hanger systems available.

HIGH EFFICACY • HIGH EFFICACY • HIGH EFFICACY • **198 LPW**

Platform


Hardware

4 CONFIGURABLE POWER CONNECTIONS
Hardwire, power cord whip and plug-and-play power connections available. Configured per order.

5 LIGHT DISTRIBUTION
Available with five light distribution options:
- No Lens
- 120° Lens General Distribution
- 50° Lens Narrow Distribution
- 90° Lens Glare Reduction
- 35° Lens Focus Distribution

6 COMPACT DESIGN
2’ and 4’ fixture body sizes in a sleek, rigid, linear unibody configuration. Built for multiple ceiling applications.

7 LIGHTWEIGHT ALUMINUM
Aluminum construction reduces ceiling grid load and maximizes heat transfer to support longer component life; allowing for quick, single person installation

8 SUPERIOR THERMAL DESIGN
Rated up to 55 °C with lens, surpassing most competition at 40-50 °C. High ambient operating temperature range option on select fixture SKUs allows fixture to operate up to 65 °C (149 °F).

9 PREMIUM COMPONENTS
Engineered with efficient and durable electronic components from the industry’s most trusted brands. 6KV/3KA surge protection standard.

NO LENS

WITH LENS

CONTROLS & ACCESSORIES
Factory or Field Installed options


Battery Back Up

Orange End Cap

Factory Installed End Mounted Integrated Control

Factory Installed Integrated Control

Available in lumen packages from 9,000 to 20,000 lumens in 2’ and 24,000 to 45,000 lumens in 4’. 120v-277v, 347v, 480v
*LED rated life based on HHSL2224LHEUNVFD L70 @ 25C ambient vs. Orion’s TLEDB5 retrofit LED tubes.

Up To 65°C | CERTIFIED | UL DAMP RATED | Buy American Act & the American Recovery and Reinvestment Act

© 2022 Orion Energy Systems, Inc. All rights reserved.