

# LED HIGH BAY

## HARRIS LED HIGH BAY UFO, GEN 4

### HHUF4 SPECIFICATIONS

#### Lumen Range / LPW

- 15,000 to 36,000 Lumens (tandem bracket available for increased lumen output up to 72,000 lumens), up to 150 LPW

#### Factory Installed Features and Options

- 120-277v or 277v-480v
- 80 CRI; 4000K or 5000K
- 6' Power Cord Included
- Fixture Available in White or Black
- Fixture Ships with Standard Eye Bolt
- 6kV/3kA Surge Protection Standard
- 20kV/10kA Additional Surge Protection Optional

#### Field Installed Options

- Additional Light Beam Control with Polycarbonate Refractor or Aluminum Reflector
- Battery Backup Kit

#### Control Types Available

- Field Installed Controls and Sensors Options
- Remote Programming Sensors
- Remote Programming Sensors with Zoning
- On Site Network Programming
- Internet/Cloud Based Network Programming

#### Certifications / Listings\*

- NSF/ANSI Standard 2
- UL/cUL Listed
- UL Wet Location Listed
- IP65 Rating
- IK10 Impact Rating
- DLC® Listed Premium

#### Mounting Options

- Surface Mounting
- Pendant Mounting
- Tandem Mounting

\*Varies by fixture configuration

