

HARRIS LED HIGH BAY STAR LINE FREEZER, GEN 1



1 FREEZER FRIENDLY HIGH BAY
The next level of HARRIS LED High Bay designed specifically to excel in performance in freezer environments. Efficacy up to 172 LPW. Provides full configurability, controllability, more energy savings, and an upgraded look.

2 4x LIFE*
HSLF1 calculated L70 rating of 208,000 hours is a minimum of 4x as long as the typical LED tube retrofit alternative.

3 VERSATILE HANGING OPTIONS
Easy clip-on cables, rigid mount brackets, pendant mount or wire hanger systems available.

-40°F



FREEZER FRIENDLY



Platform



Hardwire



NO LENS



WITH LENS

9 DURABLE PREMIUM COMPONENTS
Top tier electrical components from suppliers with brand and quality integrity.

7 LIGHTWEIGHT ALUMINUM
Aluminum construction reduces ceiling grid load and maximizes heat transfer to support longer component life. This allows for quick, single person installation minimizing facility disruption due to easy to lift fixture.

5 LIGHT DISTRIBUTION
Available with four light distribution options: No Lens, 120° Lens General Distribution, 50° Lens Narrow Distribution, and 35° Lens Focus Distribution.

8 SUPERIOR THERMAL FREEZER PERFORMANCE
The Star Line Freezer is rated down to -40°C which is ideal for freezer applications.


6 COMPACT DESIGN
2' and 4' fixture body sizes in a sleek, rigid, linear unibody configuration. Built for multiple ceiling applications.

4 CONFIGURABLE POWER CONNECTIONS
Hardwire, power cord whip and plug-and-play power connections available. Configured per order.


CONTROLS & ACCESSORIES
Factory or Field Installed options



Sensor Option**



Orange End Cap



Wireguard

Available in lumen packages from 15,000 to 20,000 lumens in 2 ft and up to 29,000 lumens in 4 ft. 120v-277v, 347v, 480v

*LED rated life based on HSLF1C1 L70 @ 25C ambient vs. Orion's TLEDB5 retrofit LED tubes.

**Preset at factory for use in cold temperatures.

