

LED TROFFER RETROFIT

HARRIS LED LDR® TROFFER RETROFIT, GEN 3

LDRE3 SPECIFICATIONS

Fixture Sizes

- 1' x 4', 2' x 2', or 2' x 4'

Lumen Range / LPW

- 2,000 to 8,000 Lumens, up to 165 LPW

Factory Installed Features and Options

- 120-277v and 347v
- 80 CRI; 3500K, 4000K, or 5000K
- Battery Backup
- Different Dimming Capacity Drivers
- Dial Dimmer
- Britex™ Coating

Field Installed Options

- Seismic Cable

Control Types Available

- Factory Installed Controls and Sensors Available
- Manual Programming Sensors
- Remote Programming Sensors
- On Site Network Programming
- Internet/Cloud Based Network Programming

Certifications / Listings*

- Buy American Act Compliant
- UL/cUL Listed
- DLC® Listed Standard
- BABA Compliant
- CA Title 20 Compliant Battery Backup Available

Mounting Options

- Standard, Plenum and Lift Bracket Kits for Recessed T-Bar Grids

Installs in minutes with quick bracket system

Dial dimmer available for field adjustment of power and lumen output option



Ultra-lightweight aluminum body for ease of single person install

Title 24 compliant seismic cable kit available that easily attaches to the fixture housing

**Varies by fixture configuration*

800.660.9340 | orionlighting.com

© 2024 Orion Energy Systems, Inc. All right reserved. The Orion logo, ISON™, TritonPro™, and Harris product names are registered trademarks of Orion Energy Systems. All other trademarks are property of their respective owners.

P-INT-XS-229 | Rev. 20241125