

LED WALLPACK

HARRIS LUMEN SELECT WALLPACK SEMI CUTOFF, GEN 2

LSWS2 SPECIFICATIONS

Fixture Sizes

- 1 Fixture Size Available



Lumen Range / LPW

- 3,000 to 19,000 Lumens, up to 162 LPW
- Each lumen package allows for field adjustment of lumen output



Factory Installed Features and Options

- 120v-277v
- 80 CRI; Field Adjustable CCT from 3000K, 4000K, and 5000K
- Bronze Color Standard
- 10kV/5kA Surge Protection Standard
- Battery Backup Available

Field Installed Options

- Light Shield Options
- Sensor Options
- Wire Guard Available
- Battery Backup Kit

Control Types Available



- Integrated Photocell Standard
- Field Installed Control Options

Certifications / Listings*

- DLC® Listed Premium
- IP65
- cULus Certified
- UL Wet Rated
- Field Adjustable Wattage/Light Output and CCT

Mounting Options

- Back-plated design with template to mount directly over a standard recessed junction box for surface mounting

*Varies by fixture configuration

Die-cast aluminum housing with powder coat finish for harsh outdoor environments

Accessible dip switches from the outside allow the user to select CCT and lumen output in the field



Heat and impact resistant borosilicate glass lens