

LED LINEAR

HARRIS LED STRIP LUMINAIRE, GEN 2

SFHC2 SPECIFICATIONS

Fixture Sizes

- 4' or 8'

Lumen Range / LPW

- 2,000 to 10,000 Lumens, up to 182 LPW

Factory Installed Features and Options

- 120v-277v
- 80 CRI; 3500K, 4000K, and 5000K
- Three Light Distribution Options: No Lens, Frosted Acrylic 2' Lens, Frosted Acrylic 3' Lens
- Multiple Power Connection Options
- Battery Backup Available

Field Installed Options

- Wireguard Kit

Control Types Available

- Factory and Field Installed Sensor and Controls Available
- Manual Programming Sensors
- Remote Programming Sensors
- Remote Programming with Zoning Sensors

Certifications / Listings*

- Buy American Act Compliant
- UL/cUL Listed
- DLC® Listed Standard
- BABA Compliant
- CA Title 20 Compliant Battery Backup Available

Mounting Options

- Surface Mounting
- Suspended Mounting

**Varies by fixture configuration*

Multiple fixture knockouts for quick connection to power

Can be tandem mounted to create electrical raceway between fixtures

Fixture comes with installation tethers to hold cover in place for one person installation

Fixture wireguard kit for field install for rugged environments that easily attaches to the fixture housing

