# LED AREA LIGHT

## ISON™ LED AREA LIGHT HIGH PERFORMANCE

## IAHP1 SPECIFICATIONS

### Fixture Sizes
- 3 Fixture Sizes Available

### Lumen Range / LPW
- 13,000 to 63,000 Lumens, up to 172 LPW

### Factory Installed Features and Options
- 120v-277v and 277v-480v
- 80 CRI; 3000K, 4000K, or 5000K
- 3 Light Distribution Types
- Bronze Color Standard. White and Black available.
- 10kV/5kA Surge Protection Standard
- Factory-Installed, Optional 7-pin Photocell Receptacle for Field Installation of Photocell

### Field Installed Options
- Light Shield Options
- Control and Sensor Options
- Photocell 120v-277v, 347v, and 480v

### Control Types Available
- IP66 Rated Bluetooth Remote Programmable

### Certifications / Listings*
- Dark Sky Compliant
- DLC® Listed Premium
- IK10 Rated
- IP66
- IP67
- cULus Certified
- UL Wet Rated
- Meets Title 24 Compliancy

### Mounting Options
- Yoke
- Trunnion
- Adjustable Arm
- Universal Pole Mount
- Slip-fitter
- Adjustable
- Wall Mount
- Slide & Lock Mount

**Varies by fixture configuration*

**Precision engineered lens made of optical-grade polycarbonate for maximum light intensity and high efficacy**

**Tool-less access to electrical components for field maintenance and installation**

**Anti-corrosion stainless steel hardware**

**Type III, IV, and Type V light distribution**

**TYPE III**

*Perimeter parking areas, parking lots, and roadways*



**TYPE IV**

*Perimeter parking areas, and parking lots*

**TYPE V**

*Intersections, parking lots, and center roadways*

800.660.9340 | orionlighting.com

© 2025 Orion Energy Systems, Inc. All right reserved. The Orion logo, ISON™, TritonPro™, and Harris product names are registered trademarks of Orion Energy Systems. All other trademarks are property of their respective owners.

P-INT-XS-175 | Rev. 20250707