



ISON™ PUREMOTION™ LIGHT, GEN 1



1 SPACE COMFORT
Increases air turnover which improves temperature variance. Reduces mold, humidity, odors, and allergens.

2 LED TECHNOLOGY
80CRI standard in 3500K, 4000K, and 5000K CCT options. Various lumen outputs available in 2'x2' and 2'x4' sizes.

3 ENERGY SAVINGS
System provide significant energy savings by reducing HVAC load and proving high efficacy LED lighting.

6 AESTHETIC, PRACTICAL DESIGN
Sleek, frosted matte lenses provide glare diffusion in the work place. Housing comes standard with Orion's Britex antimicrobial coating.


5 EASE OF INSTALLATION
Product can easily be placed in to a T-Bar recessed ceiling grid, surface mounted using H113SET bracket field install kit, or suspended mounted with bracket field install kit. Additional safety cable option for local code compliance.

4 4.5x LED LIFE*
The IPML1 LED L70 rating at 238,000 hours is over 4.5x as long as the typical LED retrofit tubes alternatives while providing more energy savings.


MOUNTING OPTIONS



Recessed Mount
(Lay-In Fixture
T-Bar Grid)



Surface Mount



Suspended Mount

Available in lumen packages from 2,000 to 6,000 lumens. 120-277v
*LED rated life based on IPML1A24D1UNVFD L70 @ 25C ambient vs. Orion's TLEDB5 retrofit LED tubes.

