

# LED VAPORTIGHT

## ISON™ LED VAPORTIGHT WIDE BODY, GEN 2

### VTOD2 SPECIFICATIONS

#### Fixture Sizes

- 2' or 4'

#### Lumen Range / LPW

- 13,000 to 38,000 Lumens, up to 167 LPW

#### Factory Installed Features and Options

- 120-277v, 347v, and 480v
- 80 CRI; 4000K or 5000K
- Frosted Acrylic Lens Standard
- Multiple Power Connection Options
- 6kV/3kA Surge Protection Standard
- 20kV/10kA Additional Surge Protection Optional
- Battery Backup
- Cold Temperature Option (-40C)

#### Control Types Available

- Factory Installed Control and Sensor Options
- Manual Programming Sensors
- Remote Programming Sensors

#### Certifications / Listings\*

- Buy American Act Compliant
- UL/cUL Listed
- UL Wet Listed
- IP67 for 4' Fixtures
- IP69 for 2' Fixtures
- IP66 When Using WSxx and WBxx Sensors
- IP65 When Using WWxx Sensor
- NEMA 4X Housing
- UL 5VA (f1) Fiberglass Housing
- High Pressure Washdown Up To 1500 PSI
- DLC® Listed Standard
- BABA Compliant
- CA Title 20 Compliant Battery Backup Available

#### Mounting Options

- Surface Mount (Standard – Factory Shipped)
- Suspended Mounting
- Rigid Mounting

\*Varies by fixture configuration

Cold temperature option for cold storage environments

Configurable Power connections for fast installation



Marine Grade Stainless Steel latches and mounting brackets to withstand corrosion

Durable acrylic lens and reinforced fiberglass body built to withstand tough environments