

LED VAPORTIGHT

ISON™ LED VAPORTIGHT WIDE BODY NSF/ANSI STANDARD 2 CERTIFIED, GEN 2

VTOD2 SPECIFICATIONS

Fixture Sizes

- 2' or 4"

Lumen Range / LPW

- 13,000 to 38,000 Lumens, up to 167 LPW

Factory Installed Features and Options

- 120-277v, 347v, and 480v
- 80 CRI; 4000K or 5000K
- Frosted Acrylic Lens Standard
- Multiple Power Connection Options
- 6kV/3kA Surge Protection Standard
- 20kV/10kA Surge Protection Available
- Battery Backup
- Cold Temperature Option (-40C)

Certifications / Listings*

- Buy American Act Compliant
- NSF/ANSI Standard 2
- UL/cUL Listed
- UL Wet Listed
- IP67 for 4' Fixtures
- IP69 for 2' Fixtures
- NEMA 4X Housing
- UL 5VA (f1) Fiberglass Housing
- High Pressure Washdown Up To 1500 PSI
- DLC® Listed Standard
- CA Title 20 Compliant Battery Backup Available

Mounting Options

- Surface Mount (Standard – Factory Shipped)
- Suspended Mounting
- Rigid Mounting

**Varies by fixture configuration*

Cold temperature option for cold storage environments

Configurable power connections for fast installation



Marine Grade Stainless Steel latches and mounting brackets to withstand corrosion

NSF Certified Marine Grade Stainless Steel latches and mounting brackets to withstand corrosion

800.660.9340 | orionlighting.com

© 2024 Orion Energy Systems, Inc. All right reserved. The Orion logo, ISON™, TritonPro™, and Harris product names are registered trademarks of Orion Energy Systems. All other trademarks are property of their respective owners.

P-INT-XS-251 | Rev. 20241125