

LED VAPORTIGHT

ISON™ LED VAPORTIGHT NARROW BODY, GEN 2

VTON2 SPECIFICATIONS

Fixture Sizes

- 4' or 8'

Lumen Range / LPW

- 3,000 to 20,000 Lumens, up to 165 LPW

Factory Installed Features and Options

- 120-277v, 347v, and 480v
- 80 CRI; 4000K and 5000K
- Acrylic, Impact Resistant, Ribbed Frosted Lens
- Multiple Power Connection Options
- 6kV/3kA Surge Protection Standard
- 20kV/10kA Additional Surge Protection Optional
- Battery Backup
- Cold Temperature Option (-40C)

Control Types Available

- Factory Installed Control and Sensor Options
- Manual Programming Sensors
- Remote Programming Sensors

Certifications / Listings*

- Buy American Act Compliant
- UL/cUL Listed
- UL Wet Listed
- IP67
- IP66 When Using WSxx and WBxx Sensors
- IP65 When Using WWxx Sensor
- NEMA 4X Housing
- UL 5VA (f1) Fiberglass Housing
- High Pressure Washdown Up To 1500 PSI
- DLC® Listed Standard
- BABA Compliant
- CA Title 20 Compliant Battery Backup Available

Mounting Options

- Surface Mounting (Standard-Factory Shipped)
- Suspended Mounting

*Varies by fixture configuration

Durable and lightweight white fiberglass body

Configurable power connections for fast installation



Cold temperature option for cold storage environments

Marine Grade Stainless Steel latches and mounting brackets to withstand corrosion

Durable, impact resistant acrylic frosted lens to withstand tough environments