

LED VAPORTIGHT

ISON™ LED VAPORTIGHT NARROW BODY NSF/ANSI STANDARD 2, GEN 2

VTON2 SPECIFICATIONS

Fixture Sizes

- 4' or 8'

Lumen Range / LPW

- 3,000 to 20,000 Lumens, up to 165 LPW

Factory Installed Features and Options

- 120-277v, 347v, and 480v
- 80 CRI; 4000K or 5000K
- Acrylic, Impact Resistant, Ribbed Frosted Lens
- Multiple Power Connection Options
- 6kV/3kA Surge Protection Standard
- 20kV/10kA Additional Surge Protection Optional
- Battery Backup
- Cold Temperature Option (-40C)

Certifications / Listings*

- Buy American Act Compliant
- NSF/ANSI Standard 2
- UL/cUL Listed
- UL Wet Listed
- IP67
- NEMA 4X Housing
- UL 5VA (f1) Fiberglass Housing
- High Pressure Washdown Up To 1500 PSI
- DLC® Listed Standard
- CA Title 20 Compliant Battery Backup Available

Mounting Options

- Surface Mounting (Standard-Factory Shipped)

**Varies by fixture configuration*



800.660.9340 | orionlighting.com

© 2024 Orion Energy Systems, Inc. All right reserved. The Orion logo, ISON™, TritonPro™, and Harris product names are registered trademarks of Orion Energy Systems. All other trademarks are property of their respective owners.

P-INT-XS-231 | Rev. 20241125