

LED TROFFER

TRITONPRO™ LED TROFFER SELECTABLE, GEN 3

LT HES3 SPECIFICATIONS

Fixture Sizes

- 2' x 2' or 2' x 4'



Lumen Range / LPW

- 2,000 to 6,000 Lumens, up to 148 LPW
- Each lumen package allows for field adjustment of lumen output



Factory Installed Features and Options

- 120-277v
- 80 CRI; Field Adjustable CCT from 3500K, 4000K, and 5000K
- Battery Backup
- Frosted Lens

Field Installed Options

- Battery Backup Kit

Certifications / Listings*

- UL/cUL Listed
- UL Listed Damp
- DLC® Listed Standard and Premium
- Certified for Insulated Plenums (Type IC)
- Field Adjustable Wattage/Light Output and CCT

Mounting Options

- Recessed Mounting for T-Bar Grid Systems

Frosted lens reduces glare and delivers uniform light across the lens



Driver with 12v AUX for use with external sensors

DLC® Certified to maximize energy and project savings through available rebates

**Varies by fixture configuration*

800.660.9340 | orionlighting.com

© 2024 Orion Energy Systems, Inc. All right reserved. The Orion logo, ISON™, TritonPro™, and Harris product names are registered trademarks of Orion Energy Systems. All other trademarks are property of their respective owners.

P-INT-XS-249 | Rev. 20241125