

LED TROFFER

TRITONPRO™ LED TROFFER SELECTABLE, GEN 4

LTHES4 SPECIFICATIONS

Fixture Sizes

- 1' x 4', 2' x 2', or 2' x 4'

Lumen Range / LPW

- 2,000 to 5,500 Lumens, up to 155 LPW
- Each lumen package allows for field adjustment of lumen output

Factory Installed Features and Options

- 120v-277v
- 80 CRI; Field Adjustable CCT from 3500K, 4000K, and 5000K
- Frosted Lens
- Battery Backup Available
- Option for Control Receptacle for Easy Sensor Installation

Field Installed Options

- Control Options
- Battery Backup Kit

Control Types Available

- Control receptacle option allows for fast and easy installation of standalone or Bluetooth Mesh sensors in the field

Certifications / Listings

- UL/cUL Listed
- UL Listed Damp
- DLC® Listed Premium
- TAA Compliant
- Certified for Insulated Plenums (Type IC)
- Field Adjustable Wattage/Light Output and CCT

Mounting Options

- Recessed Mounting for T-Bar Grid Systems
- Surface Mounting Kit Available
- Recessed Drywall Kit Available

External dip switches allow the user to select between 3 CCT and 3 lumen outputs in the field

Up to 155 LPW and DLC Listed to maximize energy and project savings through available rebates

Option for Control Receptacle for Easy Sensor Installation

Uniform light distribution across the lens