

LED HIGH BAY

TRITONPRO™ COMPACT LINEAR HIGH BAY

MLHB1 SPECIFICATIONS

Fixture Sizes

- 1', 2', 3' or 4'



Lumen Range / LPW

- 9,000 to 60,000 Lumens, up to 147 LPW



Factory Installed Features and Options

- 120-277v, 277-480v
- 80 CRI; Field Adjustable CCT 4000K or 5000K
- Three Lens Distribution Types: Polycarbonate Aisle Narrow, Polycarbonate Glare Reduction Medium, Polycarbonate Wide Distribution
- 6kV/3kA Surge Protection Standard
- Sensor Base Comes Standard
- Battery Backup

Field Installed Options

- Battery Backup Kit

Control Types Available

- Field Installed Control and Sensor Options
- Remote Programming Sensors

Certifications / Listings*

- UL/cUL Listed
- UL Damp Rated
- DLC® Listed Standard and Premium
- Field Adjustable CCT
- CA Title 20 Compliant Battery Backup Available

Mounting Options

- Surface Mounting
- Suspended Mounting
- Rigid Pendent Mounting

Compact design with optimal thermal performance for ease of handling during installation to decrease installation time and cost

External CCT Adjustable Switch

Impact resistant polycarbonate lenses

Sensor base included for ease of field install sensors



*Varies by fixture configuration

800.660.9340 | orionlighting.com

© 2024 Orion Energy Systems, Inc. All right reserved. The Orion logo, ISON™, TritonPro™, and Harris product names are registered trademarks of Orion Energy Systems. All other trademarks are property of their respective owners.

P-INT-XS-253 | Rev. 20241204