

LED VAPORTIGHT

TRITONPRO™ LED SLIMLINE LUMEN SELECT VAPORTIGHT

VTSS1 SPECIFICATIONS

Fixture Sizes

- 4' Standard



Lumen Range / LPW

- 3,500 to 7,000 Lumens, up to 149 LPW. Each lumen package allows for field adjustment of lumen output



Factory Installed Features and Options

- 120-277v
- 80 CRI; Field Adjustable CCT from 3500K, 4000K, and 5000K
- 6kV/3kA Surge Protection Standard
- Polycarbonate Frosted Lens Standard
- Battery Backup Available

Field Installed Options

- Field Installed Sensor Available
- Remote Programming Sensors

Control Types Available

- Multiple Power Connection Options

Certifications / Listings*

- UL/cUL Listed
- IP66 Ingress Protection Rating
- NEMA4X
- IK10 Impact Rating
- DLC® Listed Standard
- Field Adjustable Wattage/Light Output and CCT
- CA Title 20 Compliant Battery Backup Available

Mounting Options

- Surface Mounting (Standard Factory Shipped)
- Suspended Mounting (Standard Factory Shipped)

*Varies by fixture configuration

Robust polycarbonate enclosure in a light gray finish

Multiple knockouts for flexibility in mounting

Multiple power connection options; different whip lengths for less installation time

Stainless steel latches and mounting brackets to withstand harsh environments

Impact resistant polycarbonate lens for rugged environments that delivers a wide 120° distribution

Easy access to internal CCT and Lumen adjustment

