

LED HIGH BAY

TRITONPRO™ ROUND HIGH BAY SELECTABLE

RSHB1 SPECIFICATIONS



Lumen Range / LPW

- 16,000 to 36,000 Lumens (tandem bracket up to 72,000 lumens), up to 176LPW
- Each lumen package allows for field adjustment of lumen output



Factory Installed Features and Options

- 120-277v or 277v-480v
- 80 CRI; Field Adjustable CCT from 3500K, 4000K and 5000K
- 6' Whip Standard
- Fixture Available in White or Black
- Fixture Ships with Standard Eye Bolt
- 6kV/3kA Surge Protection Standard

Field Installed Options

- Polycarbonate Refractor or Aluminum Reflector
- Battery Back Up Kit

Control Types Available

- Field Installed Controls and Sensors Options
- Remote Programming Sensors
- Remote Programming Sensors with Zoning

Certifications / Listings*

- NSF/ANSI Standard 2
- UL/cUL Listed
- UL Wet Location Listed
- DLC® Listed Premium
- IK08 Impact Rating
- IP65 Ingress Protection Rating
- Field Adjustable Wattage/Light Output and CCT

Mounting Options

- Surface Mounting
- Suspended Mounting
- Pendant Mounting
- Tandem Mounting

The compact and durable design is installation-friendly. Available in black and white finishes

High efficacy round high bay, offering up to 176 LPW for significant energy savings

Field selectable light output up to 36,000 lumens and field selectable CCT (3500K/ 4000K/ 5000K)



Impact resistant polycarbonate lens withstands tough environments

Sensor ready for quick field installation

*Varies by fixture configuration

orion™

orionlighting.com | 1.800.660.9340

rev 07232024